



West American Rubber Company, LLC



Bilrite Ripley Operations, LLC

Material Safety Data Sheet

May be used to comply with OSHA Hazard Communication Standard, 29 CFR 1910.1200. Standard must be consulted for specific requirements

U.S. Department Of Labor

Occupational Safety and Health Administration (Non-Mandatory Form) Form Approved OMB No. 1218-0072

IDENTITY: (As used on label and list) 50-E-542	Note: Blank Spaces are not permitted. If any item is not applicable, the space must be marked to indicate that.
---	---

SECTION I

Manufacturer's Name: West American Rubber Company, LLC	Emergency Telephone Number: 714.532.3355
Address (Number, Street, City, and Zip Code)	Telephone Number for Information: 714.532.3355
750 North Main Street	Date Revised: 1/30/07
Orange, CA 92868	Date Printed: 5/30/08

SECTION II- HAZARDOUS INGREDIENTS/ IDENTITY INFORMATION

Hazardous Components (Specific Chemical Identity; Common Name(s))	OSHA PEL	ACGIH TLV	Other Limits Recommended	% Optional
NONE				

SECTION III- PHYSICAL/ CHEMICAL CHARACTERISTICS

Boiling Point:	N/A	Specific Gravity (Water=1)	1.31
Vapor Pressure (mm Hg.)	N/A	Melting Point:	N/A
Vapor Density (Air=1)	N/A	Evaporation Rate (Butyl Acetate=1)	N/A
Solubility in Water: NEGLIGIBLE			
Appearance and Odor: BLACK, SLIGHT ODOR			

SECTION IV- FIRE AND EXPLOSION HAZARD DATA

Flash Point (Method Used) N/A	Flammable Limits	LEL N/A	UEL N/A
Extinguishing Media: STANDARD FIRE EXTINGUISHING			
Special Fire Fighting Procedures: RECOMMEND USE OF SELF-CONTAINED BREATHING APPARATUS, PROTECTIVE CLOTHING AND GOGGLES			
Unusual Fire and Explosion Hazards: DENSE BLACK SMOKE CLOUDS MAY CAUSE TEARING			

Material Safety Data Sheet (Cont.) 50-E-542

SECTION V- REACTIVITY DATA

Stability	Unstable		Conditions to Avoid: N/A
	Stable	X	
Incompatibility (Materials to Avoid) N/A			
Hazardous Decomposition or Byproducts: BY COMBUSTION; OXIDES OF CARBON			
Hazardous Polymerization	May Occur		Conditions to Avoid: N/A
	Will Not Occur	X	

SECTION VI- HEALTH HAZARD DATA

Route(s) of Entry:	Inhalation? N/A	Skin? N/A	Ingestion? N/A
Health Hazards (Acute and Chronic) NONE ESTABLISHED			
Carcinogenity? N/A	NTP? N/A	IARC Monographs? N/A	OSHA Regulated? N/A
Signs and Symptoms of Exposure: NONE ESTABLISHED			
Medical Conditions Generally Aggravated by Exposure: NONE ESTABLISHED			
Emergency and First Aid Procedures: WASH EXPOSED SKIN WITH SOAP AND WATER			

SECTION VII- PRECAUTIONS FOR SAFE HANDLING AND USE

Steps to be Taken in Case Material is Released or Spilled: N/A			
Waste Disposal Method: SOLID DISPOSAL IN ACCORDANCE WITH LOCAL SOLIDS DISPOSAL PRACTICES			
Precautions to be Taken in Handling and Storing: KEEP AWAY FROM EXCESSIVE HEAT AND OPEN FLAME. STORE IN A COOL, DRY PLACE			

SECTION VIII- CONTROL MEASURES

Respiratory Protection (Specify Type) N/A			
Ventilation:	Local Exhaust: N/A	Special: N/A	
	Mechanical (General): N/A	Other: N/A	
Protective Gloves: OPTIONAL			
Other Protective Clothing or Equipment: NONE			
Work/Hygienic Practices: WASH EXPOSED SKIN WITH SOAP AND WATER AFTER PROLONGED CONTACT			

WARCO®

West American Rubber Company, LLC

BILTRITE®

Biltrite Ripley Operations, LLC

Material Safety Data Sheet

May be used to comply with OSHA
Hazard Communication Standard,
29 CFR 1910.1200. Standard must
be consulted for specific requirements

U.S. Department Of Labor

Occupational Safety and Health Administration
(Non-Mandatory Form)
Form Approved
OMB No. 1218-0072

IDENTITY: (As used on label and list) 60-E-461

Note: Blank Spaces are not permitted. If any item is not applicable,
the space must be marked to indicate that.

SECTION I

Manufacturer's Name: West American Rubber Company, LLC	Emergency Telephone Number: 714.532.3355
Address (Number, Street, City, and Zip Code)	Telephone Number for Information: 714.532.3355
750 North Main Street	Date Revised: 12/28/07
Orange, CA 92868	Date Printed: 5/4/10

SECTION II- HAZARDOUS INGREDIENTS/ IDENTITY INFORMATION

Hazardous Components (Specific Chemical Identity; Common Name(s))	OSHA PEL	ACGIH TLV	Other Limits Recommended	% Optional
NONE				

SECTION III- PHYSICAL/ CHEMICAL CHARACTERISTICS

Boiling Point:	N/A	Specific Gravity (Water=1)	1.28
Vapor Pressure (mm Hg.)	N/A	Melting Point:	N/A
Vapor Density (Air=1)	N/A	Evaporation Rate (Butyl Acetate=1)	N/A
Solubility in Water: NEGLIGIBLE			
Appearance and Odor: BLACK, SLIGHT ODOR			

SECTION IV- FIRE AND EXPLOSION HAZARD DATA

Flash Point (Method Used) N/A	Flammable Limits	LEL N/A	UEL N/A
Extinguishing Media: STANDARD FIRE EXTINGUISHING			
Special Fire Fighting Procedures: RECOMMEND USE OF SELF-CONTAINED BREATHING APPARATUS, PROTECTIVE CLOTHING AND GOGGLES			
Unusual Fire and Explosion Hazards: DENSE BLACK SMOKE CLOUDS MAY CAUSE TEARING			

Material Safety Data Sheet (Cont.) 60-E-461

SECTION V- REACTIVITY DATA

Stability	Unstable		Conditions to Avoid: N/A
	Stable	X	
Incompatibility (Materials to Avoid) N/A			
Hazardous Decomposition or Byproducts: BY COMBUSTION; OXIDES OF CARBON			
Hazardous Polymerization	May Occur		Conditions to Avoid: N/A
	Will Not Occur	X	

SECTION VI- HEALTH HAZARD DATA

Route(s) of Entry:	Inhalation? N/A	Skin? N/A	Ingestion? N/A
Health Hazards (Acute and Chronic) NONE ESTABLISHED			
Carcinogenicity? N/A	NTP? N/A	IARC Monographs? N/A	OSHA Regulated? N/A
Signs and Symptoms of Exposure: NONE ESTABLISHED			
Medical Conditions Generally Aggravated by Exposure: NONE ESTABLISHED			
Emergency and First Aid Procedures: WASH EXPOSED SKIN WITH SOAP AND WATER			

SECTION VII- PRECAUTIONS FOR SAFE HANDLING AND USE

Steps to be Taken in Case Material is Released or Spilled: N/A			
Waste Disposal Method: SOLID DISPOSAL IN ACCORDANCE WITH LOCAL SOLIDS DISPOSAL PRACTICES			
Precautions to be Taken in Handling and Storing: KEEP AWAY FROM EXCESSIVE HEAT AND OPEN FLAME. STORE IN A COOL, DRY PLACE			

SECTION VIII- CONTROL MEASURES

Respiratory Protection (Specify Type) N/A			
Ventilation:	Local Exhaust: N/A	Special: N/A	
	Mechanical (General): N/A	Other: N/A	
Protective Gloves: OPTIONAL			
Other Protective Clothing or Equipment: NONE			
Work/Hygienic Practices: WASH EXPOSED SKIN WITH SOAP AND WATER AFTER PROLONGED CONTACT			