SAFETY DATA SHEET



Date of issue/Date of revision 16 July 2020 Version 3.01

Section 1. Identification		
Product name	: 🗭 HIGH PERFORMANCE GREY	
Product code	: PCET70100	
Other means of identification	: Not available.	
Product type	: Powder.	
Relevant identified uses of	the substance or mixture and uses advised against	
Product use	: Industrial applications.	
Use of the substance/ mixture	: Coating. Paints. Painting-related materials.	
Uses advised against	: Not applicable.	
Manufacturer Emergency telephone number	 PPG Industries, Inc. One PPG Place Pittsburgh, PA 15272 (412) 434-4515 (U.S.) (514) 645-1320 (Canada) 	
	SETIQ Interior de la República: 800-00-214-00 (México) SETIQ Ciudad de México: (55) 5559-1588 (México)	
Technical Phone Number	: 1-888-774-2001 (US and Canada)	

Section 2. Hazards identification

OSHA/HCS status Classification of the substance or mixture	 This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200). COMBUSTIBLE DUSTS CARCINOGENICITY - Category 2 Percentage of the mixture consisting of ingredient(s) of unknown acute toxicity: 31.2% (Oral), 31.2% (Dermal), 93.3% (Inhalation)
GHS label elements Hazard pictograms	
Signal word Hazard statements	 Warning Suspected of causing cancer. May form combustible dust concentrations in air.

Section 2. Hazards identification

Precautionary statements	
Prevention	: Obtain special instructions before use. Wear protective gloves. Wear protective clothing. Wear eye or face protection.
Response	: IF exposed or concerned: Get medical advice or attention.
Storage	: Not applicable.
Disposal	: Dispose of contents and container in accordance with all local, regional, national and international regulations.
Supplemental label elements	 Keep container tightly closed. Keep away from heat, sparks, open flames and hot surfaces No smoking. Sanding and grinding dusts may be harmful if inhaled. Prevent dust accumulation. Emits toxic fumes when heated.
Hazards not otherwise classified	Fine dust clouds may form explosive mixtures with air. Handling and/or processing of this material may generate a dust which can cause mechanical irritation of the eyes, skin, nose and throat.

Section 3. Composition/information on ingredients

Substance/mixture	1	Mixture
Product name	:	P HIGH PERFORMANCE GREY

Ingredient name	%	CAS number
barium sulfate	≥20 - ≤34	7727-43-7
titanium dioxide	≥1.0 - ≤5.0	13463-67-7
carbon black, respirable powder	<1.0	1333-86-4

SUB codes represent substances without registered CAS Numbers.

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

If ingestion, irritation, any type of overexposure or symptoms of overexposure occur during or persists after use of this product, contact a POISON CONTROL CENTER, EMERGENCY ROOM OR PHYSICIAN immediately; have Safety Data Sheet information available. Never give anything by mouth to an unconscious or convulsing person.

Description of necessary first aid measures

Eye contact	 Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice.
Inhalation	 Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.
Skin contact	 Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognized skin cleanser. Do NOT use solvents or thinners.
Ingestion	 If swallowed, seek medical advice immediately and show this container or label. Keep person warm and at rest. Do NOT induce vomiting.

Most important symptoms/effects, acute and delayed

United States Page: 2/12

Product name CP HIGH PERFORMANCE GREY

Section 4. First aid measures

Potential acute health effe	<u>cts</u>
Eye contact	: Exposure to airborne concentrations above statutory or recommended exposure limits may cause irritation of the eyes.
Inhalation	: Exposure to airborne concentrations above statutory or recommended exposure limits may cause irritation of the nose, throat and lungs.
Skin contact	: No known significant effects or critical hazards.
Ingestion	: No known significant effects or critical hazards.
Over-exposure signs/sym	<u>otoms</u>
Eye contact	: Adverse symptoms may include the following: irritation redness
Inhalation	: Adverse symptoms may include the following: respiratory tract irritation coughing
Skin contact	: No specific data.
Ingestion	: No specific data.
Indication of immediate me	dical attention and special treatment needed, if necessary
Notes to physician	 Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
Specific treatments	No specific treatment.
Protection of first-aiders	: No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

See toxicological information (Section 11)

Section 5. Fire-fighting measures

Extinguishing media	
Suitable extinguishing media	: Use dry chemical powder.
Unsuitable extinguishing media	: Avoid high pressure media which could cause the formation of a potentially explosible dust-air mixture.
Specific hazards arising from the chemical	: Fine dust clouds may form explosive mixtures with air.
Hazardous thermal decomposition products	: Decomposition products may include the following materials: carbon oxides sulfur oxides metal oxide/oxides
Special protective actions for fire-fighters	: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.
Special protective equipment for fire-fighters	: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

For non-emergency personnel	:	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing dust. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.		
For emergency responders	:	If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".		
Environmental precautions	:	Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).		
Methods and materials for co	ont	ainment and cleaning up		
Small spill	:	Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Avoid dust generation. Do not dry sweep. Vacuum dust with equipment fitted with a HEPA filter and place in a closed, labeled waste container. Dispose of via a licensed waste disposal contractor.		
Large spill	:	Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Avoid dust generation. Do not dry sweep. Vacuum dust with equipment fitted with a HEPA filter and place in a closed, labeled waste container. Avoid creating dusty conditions and prevent wind dispersal. Dispose of via a licensed waste disposal contractor. Note: see Section 1 for emergency contact information and		

Section 7. Handling and storage

Precautions for safe handling Protective measures : Put on appropriate personal protective equipment (see Section 8). Avoid exposure obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing dust. Avoid the creation of dust when handling and avoid all possible sources of ignition (spark or flame). Prevent dust accumulation. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Electrical equipment and lighting should be protected to appropriate standards to prevent dust coming into contact with hot surfaces, sparks or other ignition sources. Take precautionary measures against electrostatic discharges. To avoid fire or explosion, dissipate static electricity during transfer by grounding and bonding containers and equipment before transferring material. Empty **Special precautions** ÷.

Section 13 for waste disposal.

containers retain product residue and can be hazardous. Do not reuse container. If this material is part of a multiple component system, read the Safety Data Sheet(s) for the other component or components before blending as the resulting mixture may have the hazards of all of its parts.

Date of issue 16 July 2020

Product name CP HIGH PERFORMANCE GREY

Section 7. Handling and storage

Advice on general occupational hygiene	: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.
Conditions for safe storage, including any incompatibilities	: Do not store below the following temperature: 5°C (41°F). Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits

Ingredient name	Exposure limits	
barium sulfate	ACGIH TLV (United States, 3/2019).	
	TWA: 5 mg/m³ 8 hours. Form: Inhalable	
	fraction	
	OSHA PEL (United States, 5/2018).	
	TWA: 5 mg/m ³ 8 hours. Form: Respirable	
	fraction	
	TWA: 15 mg/m ³ 8 hours. Form: Total dust	
itanium dioxide	OSHA PEL (United States, 5/2018).	
	TWA: 15 mg/m ³ 8 hours. Form: Total dust	
	ACGIH TLV (United States, 3/2019).	
	TWA: 10 mg/m ³ 8 hours.	
carbon black, respirable powder	ACGIH TLV (United States, 3/2019).	
	TWA: 3 mg/m ³ 8 hours. Form: Inhalable	
	fraction	
	OSHA PEL (United States, 5/2018).	
	TWA: 3.5 mg/m ³ 8 hours.	
Key to abbreviation	15	
A = Acceptable Maximum Peak	S = Potential skin absorption	
CGIH = American Conference of Governmental Industrial Hygienists.	SR = Respiratory sensitization	
C = Ceiling Limit	SS = Skin sensitization	
F = Fume	STEL = Short term Exposure limit values	
PEL = Internal Permissible Exposure Limit	TD = Total dust	
SHA = Occupational Safety and Health Administration.	TLV = Threshold Limit Value	
R = Respirable	TWA = Time Weighted Average	

Ζ = OSHA 29 CFR 1910.1200 Subpart Z - Toxic and Hazardous Substances

Consult local authorities for acceptable exposure limits.

Section 8. Exposure controls/personal protection

_		
Recommended monitoring procedures	atmosp the ven protecti Referen	roduct contains ingredients with exposure limits, personal, workplace where or biological monitoring may be required to determine the effectiveness of tilation or other control measures and/or the necessity to use respiratory we equipment. Reference should be made to appropriate monitoring standards. Ince to national guidance documents for methods for the determination of bus substances will also be required.
Appropriate engineering controls	or mist to keep limits.	ly with adequate ventilation. If user operations generate dust, fumes, gas, vapor , use process enclosures, local exhaust ventilation or other engineering controls o worker exposure to airborne contaminants below any recommended or statutory The engineering controls also need to keep gas, vapor or dust concentrations any lower explosive limits. Use explosion-proof ventilation equipment.
Environmental exposure controls	Emission they co cases,	ons from ventilation or work process equipment should be checked to ensure mply with the requirements of environmental protection legislation. In some fume scrubbers, filters or engineering modifications to the process equipment necessary to reduce emissions to acceptable levels.
Individual protection measur		
Hygiene measures	eating, Approp Wash o	nands, forearms and face thoroughly after handling chemical products, before smoking and using the lavatory and at the end of the working period. riate techniques should be used to remove potentially contaminated clothing. contaminated clothing before reusing. Ensure that eyewash stations and safety s are close to the workstation location.
Eye/face protection	Safety	glasses with side shields.
Skin protection		
Hand protection	worn at necess during noted t glove n	cal-resistant, impervious gloves complying with an approved standard should be all times when handling chemical products if a risk assessment indicates this is ary. Considering the parameters specified by the glove manufacturer, check use that the gloves are still retaining their protective properties. It should be hat the time to breakthrough for any glove material may be different for different nanufacturers. In the case of mixtures, consisting of several substances, the ion time of the gloves cannot be accurately estimated.
Body protection	perform	al protective equipment for the body should be selected based on the task being ned and the risks involved and should be approved by a specialist before g this product.
Other skin protection	Approp based o	riate footwear and any additional skin protection measures should be selected on the task being performed and the risks involved and should be approved by a ist before handling this product.
Respiratory protection	Respira hazards are exp certified	ator selection must be based on known or anticipated exposure levels, the s of the product and the safe working limits of the selected respirator. If workers bosed to concentrations above the exposure limit, they must use appropriate, d respirators. Use a properly fitted, air-purifying or air-fed respirator complying approved standard if a risk assessment indicates this is necessary.

Version 3.01

Product name CP HIGH PERFORMANCE GREY

Section 9. Physical and chemical properties

Appearance

Physical state	:	Solid.
		Powder.
Color	:	Not available.
Odor	:	Not available.
Odor threshold	:	Not available.
рН	1	Not available.
Melting point	1	Not available.
Boiling point	:	Not available.
Flash point	:	Closed cup: Not applicable.
Auto-ignition temperature	:	Not available.
Decomposition temperature	:	Not available.
Flammability (solid, gas)	:	Not available.
Lower and upper explosive (flammable) limits	:	Not available.
Evaporation rate	:	Not available.
Vapor pressure	:	Not available.
Vapor density	:	Not available.
Relative density	:	1.59
Density(lbs / gal)	:	13.27
Solubility	:	Insoluble in the following materials: cold water.
Partition coefficient: n- octanol/water	:	Not available.
Viscosity	:	Kinematic (40°C (104°F)): Not applicable.
Volatility	:	2% (v/v), 1.028% (w/w)
% Solid. (w/w)	:	98.972

Section 10. Stability and reactivity

Reactivity	: No specific test data related to reactivity available for this product or its ingredients.
Chemical stability	: The product is stable.
Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.
Conditions to avoid	: When exposed to high temperatures may produce hazardous decomposition products. Refer to protective measures listed in sections 7 and 8.
Incompatible materials	: Keep away from the following materials to prevent strong exothermic reactions: oxidizing agents, strong alkalis, strong acids.

Product name CP HIGH PERFORMANCE GREY

Section 10. Stability and reactivity

Hazardous decomposition products

: Decomposition products may include the following materials: carbon monoxide, carbon dioxide, smoke, oxides of nitrogen.

Section 11. Toxicological information

Information on toxicological effects

Acute toxicity

Product/ingredient name	Result			Species	Dose	Exposure
barium sulfate	LD50 Derm	nal		Rat	>2000 mg/kg	-
	LD50 Oral			Rat	>5000 mg/kg	-
titanium dioxide	LC50 Inhal		and mists	Rat	>6.82 mg/l	4 hours
	LD50 Derm	nal		Rabbit	>5000 mg/kg	-
aarban blook, roonirablo	LD50 Oral LD50 Derm			Rat Rabbit	>5000 mg/kg	-
carbon black, respirable powder	LD30 Dem	iai		Rabbit	>3 g/kg	-
powder	LD50 Oral			Rat	>15400 mg/kg	-
Conclusion/Summary	: There are	e no data av	ailable on th	e mixture itself.		
Irritation/Corrosion						
Conclusion/Summary						
Skin	: There are	e no data av	ailable on th	e mixture itself.		
Eyes	: There are	e no data av	ailable on th	e mixture itself.		
Respiratory	: There are	e no data av	ailable on th	e mixture itself.		
Sensitization						
Conclusion/Summary						
Skin	: There are	e no data av	ailable on th	e mixture itself.		
Respiratory	: There are	e no data av	ailable on th	e mixture itself.		
Mutagenicity						
Conclusion/Summary	: There are	e no data av	ailable on th	e mixture itself.		
Carcinogenicity						
Conclusion/Summary	: There are	e no data av	ailable on th	e mixture itself.		
Classification						
Product/ingredient name	OSHA	IARC	NTP			
titanium dioxide	-	2B	-			
carbon black, respirable powder	-	2B	-			

Carcinogen Classification code: IARC: 1, 2A, 2B, 3, 4 NTP: Known to be a human carcinogen; Reasonably anticipated to be a human carcinogen OSHA: + Not listed/not regulated: -

Reproductive toxicity		
Conclusion/Summary	: There are no data available on the mixture itself.	
Teratogenicity		
Conclusion/Summary	: There are no data available on the mixture itself.	

United States

Page: 8/12

Section 11. Toxicological information

Specific	target	organ	toxicity	<u>(single</u>	<u>exposure</u>)

Not available.

Specific target organ toxicity (repeated exposure)

Not available.

- Target organs
- : Contains material which may cause damage to the following organs: lungs, upper respiratory tract, eyes.

Aspiration hazard

Not available.

Information on the likely routes of exposure

Potential acute health effects : Exposure to airborne concentrations above statutory or recommended exposure limits Eye contact may cause irritation of the eyes. Inhalation : Exposure to airborne concentrations above statutory or recommended exposure limits may cause irritation of the nose, throat and lungs. Skin contact : No known significant effects or critical hazards. : No known significant effects or critical hazards. Ingestion Over-exposure signs/symptoms Eye contact : Adverse symptoms may include the following: irritation redness Inhalation : Adverse symptoms may include the following: respiratory tract irritation coughing Skin contact : No specific data. Ingestion : No specific data. Delayed and immediate effects and also chronic effects from short and long term exposure **Conclusion/Summary** : There are no data available on the mixture itself. Repeated exposure of the eves to a low level of dust can produce eve irritation. Repeated or prolonged inhalation of dust may lead to chronic respiratory irritation. Ingestion may cause nausea, diarrhea and vomiting. This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact. Short term exposure **Potential immediate** : There are no data available on the mixture itself. effects : There are no data available on the mixture itself. Potential delayed effects Long term exposure Potential immediate : There are no data available on the mixture itself. effects **Potential delayed effects** : There are no data available on the mixture itself. Potential chronic health effects General : Repeated or prolonged inhalation of dust may lead to chronic respiratory irritation. Carcinogenicity : Suspected of causing cancer. Risk of cancer depends on duration and level of exposure. **United States** Page: 9/12

Product name CP HIGH PERFORMANCE GREY

Section 11. Toxicological information

- **Mutagenicity** : No known significant effects or critical hazards.
 - : No known significant effects or critical hazards.
- **Developmental effects** : No known significant effects or critical hazards.
 - : No known significant effects or critical hazards.

Numerical measures of toxicity

Acute toxicity estimates

Teratogenicity

Fertility effects

Product/ingredient name	Oral (mg/ kg)	Dermal (mg/kg)	Inhalation (gases) (ppm)	(vapors)	Inhalation (dusts and mists) (mg/ I)
P HIGH PERFORMANCE GREY	N/A	5170.2	N/A	N/A	N/A
barium sulfate	N/A	2500	N/A	N/A	N/A
carbon black, respirable powder	N/A	2500	N/A	N/A	N/A

Section 12. Ecological information

Toxicity

Product/ingredient name	Result	Species	Exposure
titanium dioxide	Acute LC50 >100 mg/l Fresh water	Daphnia - Daphnia magna	48 hours

Persistence and degradability

Not available.

Bioaccumulative potential

Not available.

Mobility in soil

Soil/water partition coefficient (Koc)

: Not available.

Section 13. Disposal considerations

Disposal methods

: The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

United States Page: 10/12

Product name CP HIGH PERFORMANCE GREY

Section 13. Disposal considerations

Disposal should be in accordance with applicable regional, national and local laws and regulations.

Refer to Section 7: HANDLING AND STORAGE and Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION for additional handling information and protection of employees. Section 6. Accidental release measures

14. Transport information

	DOT	IMDG	ΙΑΤΑ
UN number	Not regulated.	Not regulated.	Not regulated.
UN proper shipping name	-	-	-
Transport hazard class (es)	-	-	-
Packing group	-	-	-
Environmental hazards Marine pollutant substances	No. Not applicable.	No. Not applicable.	No. Not applicable.

Additional information		
DOT	:	None identified.
IMDG	:	None identified.
ΙΑΤΑ	:	None identified.

Special precautions for user : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Transport in bulk according : Not applicable. to IMO instruments

Section 15. Regulatory information

United States

United States inventory (TSCA 8b) : All components are active or exempted.

SARA 302/304 SARA 304 RQ

: Not applicable.

Composition/information on ingredients

No products were found.

SARA 311/312

Classification	: COMBUSTIBLE DUSTS

CARCINOGENICITY - Category 2

Composition/information on ingredients

Product name CP HIGH PERFORMANCE GREY

Section 15. Regulatory information

Name	%	Classification
titanium dioxide carbon black, respirable powder	<1.0	CARCINOGENICITY - Category 2 COMBUSTIBLE DUSTS CARCINOGENICITY - Category 2

Additional environmental information is contained on the Environmental Data Sheet for this product, which can be obtained from your PPG representative.

California Prop. 65

WARNING: Cancer - www.P65Warnings.ca.gov.

Section 16. Other information

Hazardous Material Information System (U.S.A.)

Health : 1 * Flammability : 70 Physical hazards : 0

(*) - Chronic effects

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings and the associated label are not required on MSDSs or products leaving a facility under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered trademark and service mark of the American Coatings Association, Inc.

The customer is responsible for determining the PPE code for this material. For more information on HMIS® Personal Protective Equipment (PPE) codes, consult the HMIS® Implementation Manual.

National Fire Protection Association (U.S.A.)

Health : 1 Flammab	ility : 🔽 Instability : 0
Date of previous issue	: 6/15/2020
Organization that prepared the MSDS	: EHS
Key to abbreviations	: ATE = Acute Toxicity Estimate BCF = Bioconcentration Factor GHS = Globally Harmonized System of Classification and Labelling of Chemicals IATA = International Air Transport Association IBC = International Air Transport Association IBC = International Maritime Dangerous Goods LogPow = logarithm of the octanol/water partition coefficient MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution) N/A = Not available SGG = Segregation Group UN = United Nations

Indicates information that has changed from previously issued version.

Disclaimer

The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by PPG, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.